

AB7811

HDMI extender set via UTP Cables, max. 60m, with IR set

Extend the HDMI signal up to 60 meter maximum via one single UTP cable

- HDMI extender set 60m single UTP Cable, 3D and IR support
- Extend your HDMI connection with a maximum of 60 meters
- Maximum (3D) resolution: 1080p @ 60Hz
- Including infrared support
- Suitable for use with one UTP cable
- Compatible with HDMI High speed (HDMI 1.4a)
- Power adapters included

DESCRIPTION

The Eminent AB7811 HDMI extender kit allows you to play an HDMI signal up to 60 meters with a maximum resolution of (3D) 1080p @ 60Hz. The Extender kit contains a transmitter and a receiver to connect with HDMI cables to a source device and a TV/monitor. Use one single CAT6 UTP cable up to 60 meters to connect the transmitter with the receiver. The AB7811 is equipped with an IR set so you can easily control your source device with its standard remote control.

Display your files up to 60 meters from a source device Too much distance between your TV and media player or Blu-ray player? Choose the AB7811 Extender to play your movies remotely. The AB7811 is also a perfect solution for displaying a company presentation on a TV in the reception or cafeteria area of your office. The AB7811 plays everything without compromising video quality over a distance up to 60 meters.

Connecting your devices

The AB7811 comes with an IR set to control the HDMI source. With this IR set you can continue using the standard remote control of your source device. Connect the transmitter with an HDMI High Speed cable to your HDMI source and connect the receiver to the TV with an HDMI High Speed cable. The transmitter and receiver are connected with one single UTP cable up to 60 meters. Both the transmitter and the receiver come with an additional AC Adapter.

TECHNICAL

- Transmission Distance: max. 60m. over single Cat6 UTP cable
- CAT5e cable also supported for an resolution of 720p or lower
- Supported resolutions 50/60hz compatible: 480i/576i/480P/576P/720P/1080i/1080P
- Supported 3D format: 1080p@30/60hz
- HDMI standard: High Speed
- Audio Passthrough: DTS-HD MA, Dolby True-HD, Dolby Digital.
- IR support: IR-RX receiver / IR-TX transmitter
- Power consumption: 3W
- Power supply: 5V 1A x2
- Dimensions in mm. (WxHxD): 115x35x70
- Weight in grams: 307g (set)

LOGISTIC

- Product Weight: 308.00 g
- Retail packaging Dimension (mm): 212 x 181 x 60
- Retail packaging Weight: 633 g
- Master carton Qty: 20
- Master carton Dimension (cm): 42 x 38 x 32
- Master carton Weight: 12.50 kg

