EW5616

Pulverizador refrigerante

Pulverizador refrigerante para detetar defeitos causados pelo sobreaquecimento de painéis eletrónicos

• Atinge -45 °C
• Expõe defeitos provocados pelo sobreaquecimento
• Reduz os danos provocados pela soldadura
• 100% Ozônio amigável
• Conteúdo: 200ml

DESCRIPTION

Ewent EW5616 pulverizador refrigerante instantâneo ideal para detetar defeitos causados pelo sobreaquecimento de painéis eletrónicos e defeitos de soldadura

TECHNICAL

• Contains flammable light gases (propane-butane). Ecological and odorless product.
• Does not affect plastic materials and leaves no residual moisture
• High pressure removes dirt easily and quickly
• Spray with special valve for air flow control
• Does not contain propellants deemed harmful to ozone
• Packaging: Aerosol
• Color: Colorless
• flammability: Extremely flammable
• net content: 200ml
• storage temperature: less than 50 ° C

LOGISTIC

• Product Weigth: 155.00 g
• Retail packaging Dimension (mm): 50 x 160 x 50
• Retail packaging Weigth: 160 g
• Master carton Qty: 12
• Master carton Dimension (cm): 16 x 22 x 18
• Master carton Weigth: 2.00 kg


ewent
Cooling Spray


ewent
Cooling Spray


ewent
Cooling Spray


ewent
Cooling Spray


ewent
Cooling Spray