

EW5616

Pulverizador refrigerante

Pulverizador refrigerante para detetar defeitos causados pelo sobreaquecimento de painéis eletrónicos

- Atinge -45 °C
- Expõe defeitos provocados pelo sobreaquecimento
- Reduz os danos provocados pela soldadura
- 100% Ozônio amigável
- Conteúdo: 200ml

DESCRIPTION

Ewent EW5616 pulverizador refrigerante instantâneo ideal para detetar defeitos causados pelo sobreaquecimento de painéis eletrónicos e defeitos de soldadura

TECHNICAL

- Contains flammable light gases (propane-butane). Ecological and odorless product.
- Does not affect plastic materials and leaves no residual moisture
- High pressure removes dirt easily and quickly
- Spray with special valve for air flow control
- Does not contain propellants deemed harmful to ozone
- Packaging: Aerosol
- Color: Colorless
- flammability: Extremely flammable
- net content: 200ml
- storage temperature: less than 50 ° C

LOGISTIC

- Product Weight: 155.00 g
- Retail packaging Dimension (mm): 50 x 160 x 50
- Retail packaging Weight: 160 g
- Master carton Qty: 12
- Master carton Dimension (cm): 16 x 22 x 18
- Master carton Weight: 2.00 kg



