

EW3947

Line Interactive UPS 800 VA - 480 W with AVR

Reliable 800 VA mains power protector for office and home usage

- Line Interactive UPS 800 VA with a backup time of approximately 20 minutes @ 120 W load
- Sound alarm and LED notification during power failure, with status LEDs
- Input: 1x IEC C14 with detachable cable, Output: 1x IEC C13 + 1x EU socket type F female
- Surge, short circuit, discharge, overcharge and overload protection
- AVR function to stabilize the output voltage

DESCRIPTION

Protect your computer and valuable files against power failures and surges with the EW3947 Line Interactive UPS 800 VA with AVR and surge protection. The UPS is equipped with 1x IEC C13 output and 1x EU socket type F. The UPS notifies you with a sound alarm and LED notification during a power failure. It provides you with approximately 20 extra minutes @ 120 W load to save your files and to shut down your computer safely. The EW3947 has surge, short circuit, discharge, overcharge and overload protection.

Backup power of approx. 20 minutes @ 120 W load

The EW3947 Line Interactive UPS 800 VA has one IEC C13 output and one EU socket type F female to protect your computer and valuable files against power failures and surges. The built-in battery of the Line Interactive UPS allows you to save your files within approximately 20 minutes @ 120 W load. The output voltage will remain stable thanks to the AVR function.

Sound and LED notification during power failure

The UPS notifies you with a sound alarm and LED notification during a power failure. The UPS also notifies you when the built-in battery is running out of power. The built-in status LEDs are showing you the status. The EW3947 has surge, short circuit, discharge, overcharge and overload protection.

Easy to connect

It is very easy to connect a computer or another powered device to the EW3947. Connect the IEC C13 plug to the UPS, or put a power plug into the EU socket.

TECHNICAL

- Output Power: 800 VA/480 W
- Input: 230 V~50/60 Hz
- Output: 230 V~50/60 Hz
- Fuse: 10 A / 250 V
- Technology: Line Interactive
- Inverter Waveform: Simulated Sine wave
- Voltage stabilization: AVR (Automatic Voltage Regulation)
- Battery: 1 x 12 V / 9 Ah
- Backup time: Approx. 20 minutes for @ 120 W load
- Transfer time: less than 2-6 milliseconds
- Outlet socket: 1x IEC (C13) + 1x EU socket type F female
- Alarm function: AC fails, Low battery, Overload, Fault
- Protection: Short circuit protection, Discharge Overcharge and overload protection.
- Surge protection: 125 joules
- Control Panel: LED
- Weight: 5,0 Kg
- Dimension LxWxH: 298 x 101 x 142mm
- Power usage stand-alone: 10,5 W
- Equipped with: power cable, 1x spare fuse
- Environment: 0-90 % RH @ 0-40 °C (non-condensing)



LOGISTIC

- Product Weigth: 5250.00 g
- Retail packaging Dimension (mm): 390 x 290 x 180
- Retail packaging Weigth: 10400 g
- Master carton Qty: 2
- Master carton Dimension (cm): 36,5 x 30 x 44
- Master carton Weigth: 21.50 kg

