ewent (Eminent)

IM1195

Cat 8.1 S/FTP Networking cable, 15m

• Network cable for 25/40G Base-T Ethernet networks (40GB-capable) and downward compatible, Ethernet (10BASE-T, 100BASE-TX, 1000BASE-T)

- Cat 8.1 raw cable up to 2000 MHz / 2 GHz
- RJ45 plug with 50µ gold-plated contact
- Suitable for Power over Ethernet (PoE/PoE+)
- Double-shielded LAN/network cable: wire pair shielding + overall shielding
- Ideal for game consoles with high resolution image (4K/120Hz, 8k/60Hz) such as Playstation 5 or Xbox serie X/S

DESCRIPTION

High Speed Ethernet Cable

Cat 8.1 ethernet cable support bandwidth up to 2000MHZ and 40Gbps data transmitting speed, 26AWG Cables suitable Indoor at hyper speed without worrying about cable mess.

Universal Compatibility

The Ewent Cat 8.1 Ethernet cable works perfectly with networking switch, IP Cam, routers, Nintendo switch, ADSL, Adapters, Modem, PS3, PS4, X-box, Cloud data Server, Patch Panels, Servers, Networking Printers, Netgear, TP-link, NAS, VoIP phones, laptop, Coupler, Hubs, Keystone jack, Smart TV, iMac and other device with RJ45 connectors. Compatible with Cat7/Cat5/Cat5e/Cat6.

Protected

Double shielding (S/FTP) for dependable protection against interference and noise. Ewent Cat 8.1 cables are made without elements from halogens LSZH (Low Smoke Zero Halogen Halogens) carry risks if exposed to fire, as the elements release into the air, and if combined with water they produce a toxic acid.

TECHNICAL

- Shielding class: S/FTP (PiMF)
- Specification: CAT 8.1
- Cable type: Cat 8.1 raw cable
- Inner conductor material: CU (copper)
- Material cable sheath: LSZH
- AWG: 26/7 (stranded)
- Number of shieldings: 2 x
- Cable sheath diameter (approx.): 8.2 mm
- LSZH compliant: yes
- · Length: 15m

LOGISTIC

- Product Weigth:
- Retail packaging Dimension (mm):
- Retail packaging Weigth:
- · Master carton Qty:
- Master carton Dimension (cm):
- Master carton Weigth:

14/05/2024

Power Cables My Home Network Surveillance Streamers

pp/PC Power

Page 1/2

ewent **Eminent**

14/05/2024

Page 2/2