IM1224

Cabo de instalação CAT.6A U / UTP, LSZH, 305m

• AWG23 / 1
• CU nua sólida
• Jaqueta: LSZH cor cinza
• CPR certificado, classe Eca
• Desempenho de 500 MHz
• 10GBit Ethernet
• PoE Power over Ethernet support

DESCRIPTION

O cabo de instalação Ewent Cat.6A U/UTP segue a construção do cabo 4x2x AWG23/1 e atinge uma frequência de transmissão de até 500 MHz. A capa do cabo livre de halogênio está em conformidade com o padrão IEC 60332-1, FRNC-B, LSZH-1 e CPR Euro classe Eca. O cabo é adequado para a construção de cabeamento estruturado na área secundária e terciária. Em conformidade com as seguintes normas ISO/IEC 11801, DIN EN 50173, DIN EN 50288-11-1.

TECHNICAL

• Category: Cat.6A
• Shielded: U/UTP
• Conductor material: CU (Copper)
• Conductor size (AWG): 23/1
• Conductor type: Solid
• Jacket material: LSZH
• CPR: Eca
• Cable length: 305m
• Color: blue

LOGISTIC

• Product Weigth:
• Retail packaging Dimension (mm):
• Retail packaging Weigth:
• Master carton Qty:
• Master carton Dimension (cm):
• Master carton Weigth:

CAT.6A
U/UTP


PAIR SEPARATOR
500 MHZ BANDWIDTH
LSZH halogen free
23 AWG
Bare Copper
Cu
PURE BARE COPPER

ewent
305m