

IM1225

Matassa di cavo CAT.7 S/FTP, LSZH, 30m

- AWG23 / 1
- Cu Rame pure solido
- Guaina: LSZH colore arancio
- Certificato CPR, Classe B2ca Eca
- Prestazioni a 1200 MHz
- 10GBit Ethernet
- Supporta PoE Power over Ethernet

DESCRIPTION

Il cavo di installazione Ewent Cat.7 S/FTP segue la struttura del cavo 4x2x AWG23/1 e raggiunge una frequenza di trasmissione fino a 1200 MHz. Il rivestimento del cavo privo di alogeni è conforme allo standard IEC 60332-1, FRNC-B, LSZH-1 e CPR Euro classe Eca. Il cavo è adatto per realizzare cablaggi strutturati nel settore secondario e terziario. Conforme alle seguenti norme ISO/IEC 11801, DIN EN 50173, DIN EN 50288-11-1.

TECHNICAL


- Category: Cat.7
- Shielding: S-FTP, pairs in metal foil and braid shielding
- Conductor material: CU (Copper)
- Conductor size (AWG): 23/1
- Conductor type: Solid
- Jacket material: LSZH
- CPR: B2ca Eca
- Cable length: 30m
- Color: orange

LOGISTIC

- Product Weigth:
- Retail packaging Dimension (mm):
- Retail packaging Weigth:
- Master carton Qty:
- Master carton Dimension (cm):
- Master carton Weigth:



CAT.7
S/FTP



PURE BARE COPPER

