

IM1228

CAT.7 S/FTP Instalaltion Cable, LSZH, 305m

- AWG23/1
- Solid bare Copper Cu
- Jacket: LSZH orange color
- CPR Certified, Class B2ca Eca
- 1200Hz performance
- 10GBit Ethernet
- PoE Power over Ethernet support

DESCRIPTION

Ewent Cat.7 S/FTP installation cable is following cable construction 4x2x AWG23/1 and reaches a transmission frequency up to 1200 MHz. The halogen free cable jacket is conform to the standard IEC 60332-1, FRNC-B, LSZH-1 and CPR Euro class B2ca Eca. The cable is suitable for building structured cabling in the secondary and tertiary area. Compliant with the following standards ISO/IEC 11801, DIN EN 50173, and DIN EN 50288-4-1.

TECHNICAL

- Category: Cat.7
- Shielding: S-FTP, pairs in metal foil and braid shielding
- Conductor
- Conductor material: CU (Copper)
- Conductor size (AWG): 23/1
- Conductor type: Solid
- Diameter: 0.57mm (+/- 0.005mm)
- Outer Jacket
- Jacket material:LSZH
- CPR: B2ca Eca
- Thickness: 0.56mm (+/- 0.05mm)
- External diameter: 7.3mm (+/- 0.5mm)
- Cable length: 305m
- Color: orange


LOGISTIC

- Product Weigth:
- Retail packaging Dimension (mm):
- Retail packaging Weigth:
- Master carton Qty:
- Master carton Dimension (cm):
- Master carton Weigth:





CAT.7
S/FTP



PURE BARE COPPER

