IM1228

Matassa di cavo CAT.7 S/FTP, LSZH, 305m

• AWG23 / 1
• Cu Rame pure solido
• Guaina: LSZH colore arancio
• Certificato CPR, Classe B2ca Eca
• Prestazioni a 1200 MHz
• 10GBit Ethernet
• Suporta PoE Power over Ethernet

DESCRIPTION

Il cavo di installazione Ewent Cat.7 S/FTP segue la struttura del cavo 4x2x AWG23/1 e raggiunge una frequenza di trasmissione fino a 1200 MHz. Il rivestimento del cavo privo di alogeni è conforme allo standard IEC 60332-1, FRNC-B, LSZH-1 e CPR Euro classe Eca. Il cavo è adatto per realizzare cablaggi strutturati nel settore secondario e terziario. Conforme alle seguenti norme ISO/IEC 11801, DIN EN 50173, DIN EN 50288-11-1.

TECHNICAL

• Category: Cat.7
• Shielding: S-FTP, pairs in metal foil and braid shielding
• Conductor
• Conductor material: CU (Copper)
• Conductor size (AWG): 23/1
• Conductor type: Solid
• Diameter: 0.57mm (+/- 0.005mm)
• Outer Jacket
• Jacket material:LSZH
• CPR: B2ca Eca
• Thickess: 0.56mm (+/- 0.05mm)
• External diameter: 7.3mm (+/- 0.5mm)
• Cable length: 305m
• Color: orange


LOGISTIC

• Product Weigth:
• Retail packaging Dimension (mm):
• Retail packaging Weigth:
• Master carton Qty:
• Master carton Dimension (cm):
• Master carton Weigth:



CAT.7
S/FTP





PURE BARE COPPER