

IM1228

Cabo de instalação CAT.7 S / FTP, LSZH, 305m

- AWG23 / 1
- CU nua sólida
- Jaqueta: LSZH cor laranja
- CPR certificado, classe B2ca Eca
- Desempenho de 1200 MHz
- 10GBit Ethernet
- PoE Power over Ethernet support

DESCRIPTION

O cabo de instalação Ewent Cat.7 S/FTP segue a construção do cabo 4x2x AWG23/1 e atinge uma frequência de transmissão de até 1200 MHz. A capa do cabo livre de halogênio está em conformidade com o padrão IEC 60332-1, FRNC-B, LSZH-1 e CPR Euro classe Eca. O cabo é adequado para a construção de cabeamento estruturado na área secundária e terciária. Em conformidade com as seguintes normas ISO/IEC 11801, DIN EN 50173, DIN EN 50288-11-1.

TECHNICAL

- Category: Cat.7
- Shielding: S-FTP, pairs in metal foil and braid shielding
- Conductor
- Conductor material: CU (Copper)
- Conductor size (AWG): 23/1
- Conductor type: Solid
- Diameter: 0.57mm (+/- 0.005mm)
- Outer Jacket
- Jacket material:LSZH
- CPR: B2ca Eca
- Thickness: 0.56mm (+/- 0.05mm)
- External diameter: 7.3mm (+/- 0.5mm)
- Cable length: 305m
- Color: orange


LOGISTIC

- Product Weigth:
- Retail packaging Dimension (mm):
- Retail packaging Weigth:
- Master carton Qty:
- Master carton Dimension (cm):
- Master carton Weigth:





CAT.7
S/FTP



PURE BARE COPPER