

EW3992**65W GaN USB Charging Station with 2 outlets extender**

With 2 outlets extender and 2 Type-C and USB ports Surge&Overcurrent and Children protection. Power for 6 devices

- Compact desktop charger supports USB-C, USB-A and PPS and 2 Schuko outlets
- Power strip with surge and overcurrent protection. 65W Max High-Speed charging
- Equipped with 2 Usb ports and 2 Type-C
- Universal compatibility for all USB powered devices like Smartphone/Tablets, Notebooks, Laptops, Macbook, Bluetooth earphone, e-reader, portable speakers, hair dryer, electric shaver and other
- Power for to 6 devices at the same time. Child safety protection on each port

DESCRIPTION

65W GaN USB Charging Station and Desktop Power strip has a PPS (Programmable Power supply) that is a standard that refers to the advanced charging technology for USB-C devices. It can modify voltage and current in real time by feeding maximum power based on a device's charging status. PPS main advantage over other standards is its capability to lower conversion loss during charging. This means tha less heat is generated, which lenghtens the device battery's lifespan.

Ewent EW3992 chargin station is GaN Fast. GaN stands for Gallium Nitride which is a type of material used to make power electronics. GaN uses the material to increase the efficiency of the charger and reduce the size and weight of the charger. PD stands for Power Delivery which is a technology that allows devices to be charged at a higher wattage allowing for faster charging time.

Advantages of GaN charger:

Higher efficiency: can convert AC power to DC power with higher efficiency than silicon-based chargers.

Faster charging: can charger devices faster than traditional chargers

Smaller size: can operate at higher frequency allowing compact size

Lower heat dissipation: reduces the need for heat sink and fans

Lower electromagnetic Interference (EMI): due to high frequency operation, GaN Chargers generates less Electromagnetic Interference

TECHNICAL

- Power: max 3840W, 16A
- Input: AC 100-240V 50/60Hz 16A Max
- Outlets: 2x Type F female 16A 45° angle
- USB-C1/2 Output: 5V/3A, 9V/3A, 12V/3A, 15V3A, 20V/3.25A, 65W Max; PPS: 3.3-20V/3A
- USB-A1 Output: 5V/4.5A, 5V/3A, 9V/2.6A, 12V/2A
- USB-A2 Output: 5V/2.4A
- USB-C1 + USB-C2 + USB-A1 + USB-A2 Output: 45W+15W+5W
- Plug Connector: Type CEE 7/7 16A
- Child protection: Yes
- Protection: Overcurrent and surge protection
- Cable: H05VV-F 3G 1.0 mm2
- Cable lenght: 1,5 mt
- Weight: 453gr
- Dimensions: 75x46x116 mm
- Colour: Black
- Material: Plastic + ABS

LOGISTIC

- Product Weighth:
- Retail packaging Dimension (mm):
- Retail packaging Weighth:
- Master carton Qty:
- Master carton Dimension (cm):
- Master carton Weighth:

