EW1564

Fascette in nylon nero, 200 mm x 2,5 mm

• Set di fascette (100 pezzi) in poliammide altamente robusto per uso interno ed esterno, resistente ai raggi UV (UV ASTM D6779).
• Utilizzo in ingegneria meccanica, ingegneria elettrica, artigianato, edilizia, agricoltura, orticoltura e per tutti gli appassionati di fai da te
• Resistente a: grassi, detergenti, prodotti raffinati, solventi clorurati, alcoli e fenolo.
• Il prodotto soddisfa tutti gli standard europei, è certificato UL.
• Resistenza alle alte temperature: da -40 °C a +85 °C (temperatura di applicazione: -40 °C / +85 °C, temperatura di installazione: -10 °C / +60 °C, temperatura massima di esercizio: +/-60 °C, temperatura di fusione +256 °C.

DESCRIPTION

TECHNICAL

LOGISTIC

• Product Weigth:
• Retail packaging Dimension (mm):
• Retail packaging Weigth:
• Master carton Qty:
• Master carton Dimension (cm):
• Master carton Weigth:


x100
pieces




Desirable Design
self-locking fastener design binds multiple cables as a whole
53mm maximum
bundle diameter


Premium Quality & Sturdy Texture
super strong & durable nylon supports up to 8kg weight capacity
8kg


Versatility
used under indoor & outdoor settings for multiple purposes
Multi-purpose


Chemical Resistance
resistant to chemical substance of low intensity
Weak Alkali


UV & Heat Resistance
resistant to UV & high temperature
Against UV Rays
UV
UV-resistant
Against Heat
high temperature resistant


Maximum application
diameter: 53mm
53mm
250mm
Thickness:
0.8mm
Strength tensile is decided by width and thickness