EW1564

Oraganizador de cabo de nylon preto, 200mm x 2.5mm

• Conjunto de abraçadeiras (100 peças) feito de poliamida altamente robusta para uso interno e externo, resistente a UV (UV ASTM D6779).
• Uso em engenharia mecânica, engenharia elétrica, artesanato, construção, agricultura, horticultura, bem como para todos os entusiastas de bricolage e entusiastas de bricolage.
• Resistente a: gorduras, detergentes, produtos refinados, solventes clorados, álcoois e fenol.
• O produto cumpre todas as normas europeias, é certificado UL.
• Resistência a altas temperaturas: de -40 °C a +85 °C (temperatura de aplicação: -40 °C / +85 °C, temperatura de instalação: -10 °C / +60 °C, temperatura máx. de trabalho: +/-60 °C, temperatura de fusão +256 °C.

DESCRIPTION

TECHNICAL

LOGISTIC

• Product Weigth:
• Retail packaging Dimension (mm):
• Retail packaging Weigth:
• Master carton Qty:
• Master carton Dimension (cm):
• Master carton Weigth:

x100
pieces

Desirable Design
self-locking fastener design binds multiple cables as a whole
53mm maximum
bundle diameter

Premium Quality & Sturdy Texture
super strong & durable nylon supports up to 8kg weight capacity
8kg


Versatility
used under indoor & outdoor settings for multiple purposes
Multi-purpose

Chemical Resistance
resistant to chemical substance of low intensity
Weak Acid
Weak Alkali


UV & Heat Resistance
resistant to UV & high temperature
Against UV Rays
UV
UV-resistant
Against Heat
high temperature resistant


Maximum application
diameter: 53mm
53mm
200mm
Thickness:
0.8mm
4.8mm
Strength tensile is decided by width and thickness