EW1319

USB-C and QC3.0 Fast Charger 20W

• USB-C smartphone/tablet charger 20 Watt for fast charging: up to 50% charged in 30 minutes
• Charge smartphones and tablets with USB-C and USB-A
• Designed for next generation iPhones including iPhone 15/14 and for Android Power Delivery enabled devices
• Charging stops automatically when the battery is full
• With 1x USB-C Power Delivery port and 1x QC3.0 USB-A port
• Charge two devices simultaneously
• Compact design

DESCRIPTION

Charge your next generation Apple (including iPhone 15) and Android smartphone or tablet with the EW1319 20 Watt USB-C Fast Charger equipped with Power Delivery and USB-A QC3.0. This powerful yet compact USB-C charger is easy to take along. The USB-C charger stops charging automatically when the battery is full.
For Apple devices
The latest iPhones only include a charging cable. A USB-C charger isn't included. The EW1319 USB-C and QC3.0 Fast Charger 20W charger that is designed to charge the latest iPhones. Connect your iPhone to the Ewent 20W USB-C and QC3.0 Fast Charger charger and your smartphone will be charged up to 50% in only 30 minutes.
Android devices with Power Delivery support
Use the EW1319 USB-C and QC3.0 Fast Charger 20W to charge your Android smartphone/tablet with Power Delivery and QC 3.0 support. The USB charger negotiates with your smartphone/tablet to find the suitable charging profile.
Standard PPS Technology
20W USB-C + QC3.0 Charger has a PPS (Programmable Power supply) that is a standard that refers to the advanced charging technology for USB-C devices. It can modify voltage and current in real time by feeding maximum power based on a device's charging status. PPS main advantage over other standards is its capability to lower conversion loss during charging. This means tha less heat is generated, which lenghtens the device battery's lifespan.

TECHNICAL

• Max. output power: 20.0 W
• Output USB-C:
• 5.0V ⍰ 3.0A 15.0W Max,
• 9.0V ⍰ 2.22A 20.0W Max,
• 12.0V ⍰ 1.67A 20.0W Max.
• PPS1:3.3-5.9V ⍰3.0A 17.7W Max or
• PPS2:3.3-11.0V ⍰1.8A 19.8W Max
• Output USB-A QC3.0:
• 5.0V ⍰ 3.0A 15.0W Max,
• 9.0V ⍰ 2.0A 18.0W Max,
• 12.0V ⍰ 1.5A 18.0W Max
• USB-A + USB-C: 5.0V ⍰ 3.6A 18.0W Max
• Input voltage: 100 - 240 V AC 0,5A Max
• Power Delivery ports: 1x
• USB-C support: PD2.0/PD3.0 /PPS /QC4+/QC2.0 /QC3.0 /FCP/AFC
• QC3.0 Port: 1x
• USB-A supports: QC2.0 /QC3.0
• Colour: Black
• Input connector: CEE 7/16 (Euro) male
• Protection: Over Current Protection; Over Voltage Protection; Over Temperature Protection; Over Power Protection

• Dimensions: 43x26x42mm
• Weight: 55g

LOGISTIC

• Product Weigth:
• Retail packaging Dimension (mm):
• Retail packaging Weigth:
• Master carton Qty:
• Master carton Dimension (cm):
• Master carton Weigth:



















