

EW1325_R1

Compact GaN USB-C PD and USB-A QC Charger 30W for fast charging

- USB-C smartphone/tablet charger 30 Watt for fast charging: up to 65% charged in 30 minutes
- Charge smartphones and tablets with USB-C and USB-A
- Designed for next generation iPhones including iPhone 15/14 and for Android Power Delivery enabled devices
- Charging stops automatically when the battery is full
- With 1x USB-C Power Delivery port (featuring updated PPS2 mode: 3.3-11.0V □ 2.0A 20.0W Max) and 1x QC3.0 USB-A port. Charge two devices simultaneously
- Compact design with lightweight build (60g)

DESCRIPTION

Charge your next generation Apple (including iPhone 15/14) and Android smartphone or tablet with the EW1325_R1 30 Watt USB-C Fast Charger equipped with Power Delivery and USB-A QC3.0. This powerful yet compact USB-C charger, weighing only 60g, is easy to take along. The USB-C charger stops charging automatically when the battery is full.

For Apple devices

The latest iPhones only include a charging cable; a USB-C charger isn't included. The EW1325_R1 USB-C and QC3.0 Fast Charger 30W is designed to charge the latest iPhones. Connect your iPhone to the Ewent 30W USB-C and QC3.0 Fast Charger and your smartphone will be charged up to 65% in only 30 minutes.

Android devices with Power Delivery support

Use the EW1325_R1 USB-C and QC3.0 Fast Charger 30W to charge your Android smartphone/tablet with Power Delivery and QC 3.0 support. The USB charger negotiates with your smartphone/tablet to find the suitable charging profile.

Standard PPS Technology

The 30W USB-C + QC3.0 Charger features PPS (Programmable Power Supply), an advanced charging technology standard for USB-C devices. It can modify voltage and current in real time by providing maximum power based on the device's charging status. The main advantage of PPS over other standards is its capability to reduce conversion loss during charging, which means less heat is generated and therefore extends the device battery's lifespan.

This model supports updated PPS2 mode: 3.3-11.0V □ 2.0A 20.0W Max.

TECHNICAL

- Output USB-C:
 - 5.0V □ 3.0A 15.0W Max,
 -
 - 9.0V □ 3.0A 27.0W Max,
 -
 - 12.0V □ 2.5A 30.0W Max,
 -
 - 15.0V □ 2.0A 30.0W Max,
 -
 - 20.0V □ 1.5A 30.0W Max
 -
- PPS1: 3.3-11.0V □ 3.0A 30.0W Max or
-
- PPS2: 3.3-11.0V □ 2.0A 20.0W Max (updated)
-
- Output USB-A QC3.0:
 - 5.0V □ 3.0A 15.0W Max,
 -
 - 9.0V □ 3.0A 27.0W Max,



-
- 12.0V  2.5A 30.0W Max,
-
- 20.0V  1.5A 30.0W Max
-
- USB-A + USB-C: 5.0V  3.0A 15.0W Max
- Input voltage: 100 - 240 V AC 1.0A Max
- Power Delivery ports: 1x
- USB-C supports: PD2.0/PD3.0 /PPS /QC4+/QC2.0 /QC3.0 /FCP /AFC
- QC3.0 Port: 1x
- USB-A supports: QC2.0 /QC3.0
- Colour: White
- Input connector: CEE 7/16 (Euro) male
- Protection: Over Current Protection; Over Voltage Protection; Over Temperature Protection; Over Power Protection
- Dimensions: 45x26x88mm
- Weight: 60g

LOGISTIC

- Product Weigth:
- Retail packaging Dimension (mm):
- Retail packaging Weigth:
- Master carton Qty:
- Master carton Dimension (cm):
- Master carton Weigth:



