

## EW1333

### 65W GaN Fast 3-port (2 USB-C PD and 1 USB-A QC) charger, Compact Design

- Charge your next-generation Apple devices (including iPhone 17, iPad, and MacBook) and Android devices
- 65-Watt USB-C smartphone/tablet and notebook charger for fast charging: up to 75% charge in 30 minutes
- Supports USB-C Power Delivery 3.0 fast charging. Charges smartphones and tablets with 2 USB-C ports and 1 QC 3.0 USB-A port
- Designed for newest generation iPhones, including iPhone 17, and Android Power Delivery-enabled devices, as well as notebooks, MacBooks, iPads, Bluetooth headphones, tablets, power banks, and even game consoles
- Powerful charging performance in a compact design thanks to GaN Fast technology
- Charging stops automatically when the battery is full
- Equipped with built-in protection that protects connected devices from over current, over load, over voltage, and Temperature control
- With 2 USB-C Power Delivery ports and 1 USB-A QC 3.0 port
- Charges three devices simultaneously
- Compact design

#### DESCRIPTION

Charges three devices simultaneously

Charge your MacBook and your iPhone and AirPods at the same time with the Ewent EW1333 65W 3-Port Charger (2 USB-C PD Ports + 1 QC 3.0 USB-A Port). Get up to 65W of power when using a single USB-C port. This powerful yet compact USB-C charger is easy to carry around. The USB-C charger automatically stops charging when the battery is full.

For Apple devices (including iPhone 17)

The latest iPhones only include a charging cable. A USB-C charger is not included. The EW1333 2xUSB-C and USB-A Fast Charger 65W is designed to charge the latest iPhones and Macbook. Connect your iPhone to the Ewent 65W USB-C and USB-A Fast Charger and your smartphone will charge up to 75% in just 30 minutes.

Android devices with Power Delivery support

Use the EW1333 65W 2xUSB-C and QC3.0 fast charger to charge your Android smartphone/tablet or laptop/Notebook with Power Delivery support. The USB charger negotiates with your smartphone/tablet to find the appropriate charging profile.

GaN Fast Technology

The Ewent EW1333 charger is GaN Fast. GaN stands for Gallium Nitride which is a type of material used to make power electronics. GaN uses the material to increase magazine efficiency and reduce magazine size and weight. PD stands for Power Delivery, a technology that allows devices to be charged at a higher power allowing for faster charging times.

Advanced PPS Technology

The 65W 2xUSB-C + QC3.0 fast charger features PPS (Programmable Power Supply), an advanced USB-C charging standard that dynamically adjusts voltage and current in real time to deliver maximum power based on your device's charging status. Compared to other standards, PPS reduces conversion losses during charging, generating less heat and thereby extending your device's battery lifespan.

Compact Design

The streamlined design fits perfectly into any environment, such as an office or home; yet compact and easy to take with you on the go!



## TECHNICAL

- Max. output power: 65.0 W
- 
- Output USB-C1:
  - 5.0V □ 3.0A 15.0W Max,
  - 9.0V □ 3.0A 27.0W Max,
  - 12.0V □ 3.0A 36.0W Max,
  - 15.0V □ 3.0A 45.0W Max,
  - 20.0V □ 3.25A 65.0W Max
- PPS: 5-11V□3.0A 33W
- 
- Output USB-C2:
  - 5.0V □ 3.0A 15.0W Max,
  - 9.0V □ 2.0A 18.0W Max,
  - 12.0V □ 1.5A 18.0W Max,
- PPS: 3-5V□3.0A 15W, 3-11V□1A 11W
- 
- 
- Output USB-A:
  - 5.0V □ 3.0A 15W Max,
  - 9.0V □ 2.0A 18W Max,
  - 12.0V □ 1.5A 18W Max
- 
- USB-C1+USB-C2:
  - PD45W+PD18W
  - 5.0V/3.0A, 9.0V/3.0A, 12.0V/3.0A, 15.0V/3.0A, 20.0V/2.25A 45.0W
  - 5.0V/3.0A, 9.0V/2.0A, 12.0V/1.5A 18.0W
- 
- USB-C1+USB-A:
  - PD45W+5V3A
  - 5.0V/3.0A, 9.0V/3.0A, 12.0/3.0A, 15.0/3.0A, 20.0V/2.25A 45.0W
  - 5.0V/3.0A 15.0W
- 
- USB-C2+USB-A:
  - 5.0V/3.0A 15W
- 
- USB-C1+USB-C2+USB-A Output: PD45W+15W
  - 5.0V/3.0A, 9.0V/3.0A, 12.0/3.0A, 15.0V/3.0A, 20.0V/2.25A 45.0W
  - 5.0V/3.0A, 15.0W
- 
- Input voltage: 110 - 240 V AC 1,2A Max
- 
- Power Delivery ports: 2x
- USB-C supports: PD3.0, PPS, QC2.0/3.0/4+, AFC, FCP, SCP, Apple 2.4A, BC1.2
- 
- USB-A Port: 1x
- USB-A supports: QC3.0
- 
- Colour: White
- Input connector: CEE 7/16 (Euro) male
- 
- Protection: Over Current Protection; Over Voltage Protection; Over Temperature Protection; Over Load Protection
- 
- Dimensions: 59x32x94mm

- Weight: 97g

## LOGISTIC

- Product Weight: 97.00 g
- Retail packaging Dimension (mm): 80 x 145 x 35
- Retail packaging Weight: 120 g
- Master carton Qty: 100
- Master carton Dimension (cm): 38 x 41 x 25
- Master carton Weight: 12.00 kg

