

Safety Data Sheet dated 5/5/2020, version 3

1.1. Product identifier Mixture identification:	
Trade name:	DETERGENT FOR FABRICS AND SURFACES SPRAY
Trade code:	EW5675
	f the substance or mixture and uses advised against
Recommended use:	The substance of mixture and uses advised against
PRODUCTS FOR AIR CONDI	TIONING SYSTEMS
spray cleaner	
Uses advised against:	
do not use on humans and ani	imals
do not use for purposes other	
1.3. Details of the supplier of the	
Company:	
	ocevia, 12 – 39057 – Appiano sulla strada del Vino (BZ)
ALBINA S.R.L. – info@e	
Competent person responsible	
info@ewent-online.com	
1.4. Emergency telephone nur	
	ano 02 66101029 (CAV Ospedale Niguarda Ca' Granda -Milano)
Centro Antiveleni di Pav	via 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia)
Centro Antiveleni di Ber	gamo 800 883300 (CAV Ospedali Riuniti - Bergamo)
Centro Antiveleni di Fire	enze 055 7947819 (CAV Ospedale Careggi - Firenze)
Centro Antiveleni di Ror	na 06 3054343 (CAV Policlinico Gemelli - Roma)
Centro Antiveleni di Ror	na 06 49978000 (CAV Policlinico Umberto I - Roma)
Centro Antiveleni di Nar	ooli 081 7472870 (CAV Ospedale Cardarelli - Napoli)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture EC regulation criteria 1272/2008 (CLP):

Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

Warning, Eye Irrit. 2, Causes serious eye irritation.

Warning, Skin Sens. 1, May cause an allergic skin reaction.

Warning, STOT SE 3, May cause drowsiness or dizziness.

Adverse physicochemical, human health and environmental effects:

No other hazards 2.2. Label elements Hazard pictograms:



Danger

MIXIPAIGIEN/3 Page n. 1 of 13

Hazard statements:

H222+H229 Extremely flammable aerosol. Pressurized container: may burst if heated.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water/...

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor/... if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions: None

Contains

propan-2-ol; isopropyl alcohol; isopropanol

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)

alpha-Terpineol acetate - FEMA: May produce an allergic reaction.

derogation 1.3.3. Aerosols and containers fitted with a sealed spray device and containing

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

SECTION 10.3

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Num		Classification
>= 30% - < 40%	propane	Index number: CAS: EC: REACH No	74-98-6 200-827-9	 2.2/1 Flam. Gas 1 H220 2.5 Press. Gas H280

		[ر ب
			2119486944-	
>= 20% -	ethanol; ethyl alcohol	Index	21-0046 603-002-00-5	
<pre>>= 20% - < 25%</pre>		number:	003-002-00-5	2.6/2 Flam. Liq. 2 H225
× 2070		CAS:	64-17-5	3.3/2 Eye Irrit. 2 H319
		EC:	200-578-6	
		REACH No.:		
			2119457610-	
>= 20% -	Hydrocarbons, C4;	Index	43-xxxx 649-113-00-2	
< 25%	Petroleum gas	number:	049-113-00-2	2.5 Press. Gas H280
2070	l ou olouin guo	CAS:	87741-01-3	😍 2.2/1 Flam. Gas 1 H220
		EC:	289-339-5	DECLK (CLP)*
		REACH No.:		
			2119480480-	
>= 20% -	propan-2-ol; isopropyl	Index	41-xxxx 603-117-00-0	
< 25%	alcohol; isopropanol	number:	003-117-00-0	2.6/2 Flam. Liq. 2 H225
		CAS:	67-63-0	3.3/2 Eye Irrit. 2 H319
		EC:	200-661-7	🗘 3.8/3 STOT SE 3 H336
		REACH No.:		
			2119457558- 25-xxxx	
>= 0.1%	1-methoxy-2-propanol;	Index	603-064-00-3	
- <	monopropylene glycol	number:		2.6/3 Flam. Liq. 3 H226
0.25%	methyl ether	CAS:	107-98-2	😍 3.8/3 STOT SE 3 H336
		EC:	203-539-1	
		REACH No.:	01- 2119457435-	
			35-xxxx	
>= 0.1%	butanone; ethyl methyl	Index	606-002-00-3	2.6/2 Flam. Liq. 2 H225
- <	ketone	number:		
0.25%		CAS:	78-93-3	3.3/2 Eye Irrit. 2 H319
		EC:	201-159-0	♥ 3.8/3 STOT SE 3 H336
>= 0.1%	alaba Taminaal	CAS:	80-26-2	EUH066
>= 0.1%	alpha-Terpineol acetate - FEMA	CAS:	80-26-2	3.4.2/1 Skin Sens. 1 H317
0.25%				4.1/C2 Aquatic Chronic 2 H411
481 ppm	reaction mass of: 5-	Index	613-167-00-5	3.2/1B Skin Corr. 1B H314
	chloro-2-methyl-4-	number:	55965-84-9	• 3.4.2/1-1A-1B Skin Sens.
	isothiazolin-3-one [EC no. 247-500-7]; and 2-	CAS:	55905-64-9	1,1A,1B H317
	methyl-2H -isothiazol-			4.1/A1 Aquatic Acute 1 H400
	3-one [EC no. 220-			
	239-6] (3:1)			4.1/C1 Aquatic Chronic 1 H410
				😤 3.1/3/Oral Acute Tox. 3 H301
				😤 3.1/3/Dermal Acute Tox. 3
				H311
				3.1/3/Inhal Acute Tox. 3 H331

*DECLK (CLP): This substance is classified in accordance with Note K, Annex VI of EC Regulation CE 1272/2008. The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w 1,3-butadiene (Einecs No 203-450-8). If the substance

is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 should apply. This note applies only to certain complex oil-derived substances in Part 3.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

- 4.2. Most important symptoms and effects, both acute and delayed
 - For symptoms and effects due to the contained substances see chapter 11
- 4.3. Indication of any immediate medical attention and special treatment needed
 - In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment:
 - Follow the doctor's instructions.

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
 - Suitable extinguishing media:
 - CO2 or Dry chemical fire extinguisher.
 - Extinguishing media which must not be used for safety reasons: Water.
- 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. Do not inhale explosion and combustion gases. Hazardous combustion products: Organic irritants

Carbon monoxide Organic irritants

- Particulates
- 5.3. Advice for firefighters

Normal elements for fire fighting, such as a self-contained compressed air open-circuit respirator (EN 137), fire-retardant suit (EN469), flame-retardant gloves (EN 659) and fire boots (HO A29 or A30).

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Keep containers cool with water spray.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

MIXIPAIGIEN/3 Page n. 4 of 13

Wear personal protection equipment. Remove all sources of ignition.

Remove all sources of ignition Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up

For containment:

Limit in case of leakage of significant quantities of product. Contain the spread of small quantities of product with earth, sand or other inert absorbent material.

For cleaning up:

Wash with plenty of water.

Wet clean or vacuum up solids.

Clear spills immediately

Other information:

Don't use a brush or compressed air for cleaning surfaces or clothing.

6.4. Reference to other sections See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhaltion of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Use localized ventilation system.

Advice on general occupational hygiene:

Do not eat, drink or smoke when using this product.

Contamined clothing should be changed before entering eating areas.

- Wash hands after use
- 7.2. Conditions for safe storage, including any incompatibilities

store in a cool, well ventilated place, away from heat, flames, sparks or other sources of ignition

keep only in the original container away from sunlight neighborhoods

avoid contact with skin and eyes, inhalation of vapours/mists/dusts.

do not use empty containers before they are cleaned.

contaminated clothing must be replaced before entering the dining areas.

at work do not eat or drink.

do not smoke

avoid the accumulation of electrostatic charges.

Always keep in a well ventilated place.

Store at below 50 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

Keep away from acids.

MIXIPAIGIEN/3 Page n. 5 of 13

Keep away from combustible materials. Keep away from water or from damp surroundings. See subsection 10.5 Instructions as regards storage premises: Cool and adequately ventilated. Safety electric system.

7.3. Specific end use(s) None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters
propane - CAS: 74-98-6
ACGIH
ethanol; ethyl alcohol - CAS: 64-17-5
ACGIH - STEL: 1000 ppm
propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm
1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2
EU - TWA(8h): 375 mg/m3, 100 ppm - STEL: 563 mg/m3, 150 ppm
ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm
butanone; ethyl methyl ketone - CAS: 78-93-3
EU - TWA(8h): 600 mg/m3, 200 ppm - STEL: 900 mg/m3, 300 ppm
ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm DNEL Exposure Limit Values
propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
Consumer: 319 mg/kg/d - Exposure: Human Dermal - Frequency: Long Term
(repeated)
Consumer: 89 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term
(repeated)
Consumer: 26 mg/kg/d - Exposure: Human Oral - Frequency: Long Term (repeated)
Consumer: 888 mg/kg/d - Exposure: Human Dermal - Frequency: Long Term, systemic
effects
Consumer: 500 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term,
systemic effects
butanone; ethyl methyl ketone - CAS: 78-93-3
Worker Professional: 1161 mg/kg/d - Consumer: 412 mg/kg/d - Exposure: Human
Dermal - Frequency: Long Term, systemic effects
Worker Professional: 600 mg/l - Consumer: 106 mg/l - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Consumer: 31 mg/kg/d - Exposure: Human Oral - Frequency: Long Term, systemic
effects
PNEC Exposure Limit Values
propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
Target: Fresh Water - Value: 140.9 mg/l
Target: Marine water - Value: 140.9 mg/l
Target: Freshwater sediments - Value: 552 mg/kg
Target: Marine water sediments - Value: 552 mg/kg
Target: Soil (agricultural) - Value: 28 mg/kg
butanone; ethyl methyl ketone - CAS: 78-93-3
Target: Freshwater sediments - Value: 284.74 mg/kg
Target: Marine water sediments - Value: 284.74 mg/kg
Target: Soil (agricultural) - Value: 22.5 mg/kg Target: Fresh Water - Value: 55.8 mg/l
Target: Marine water - Value: 55.8 mg/l
rarget. Marine water - value. 00.0 mg/r

MIXIPAIGIEN/3 Page n. 6 of 13

8.2. Exposure controls

Eye protection:

Eye glasses with side protection. EN 166

Protection for skin:

Wear work clothes with long sleeves and protective footwear for professional use of category II (ref.Directive 89/686 / CEE and norm EN ISO 20344). Wash with soap and water after removing protective clothing.

Protection for hands:

Protect hands with category II work gloves (ref. Directive 89/686 / EEC and standard EN 374). Use PVC or nitrile rubber gloves.

Respiratory protection:

if the TLV thresholds are exceeded, use a mask with filter type A (against vapors of organic compounds) in accordance with EN 141.

Thermal Hazards:

Do not expose to temperatures exceeding 50° c.

Environmental exposure controls:

emissions from production processes, including those from ventilation equipment should be inspected for the purposes of enforcement of environmental protection

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Spray can		
Odour:	perfumed of		
	essence		
Odour threshold:	Not Relevant		
pH:	Not Relevant		
Melting point / freezing point:	Not Relevant		
Initial boiling point and boiling range:	Not Relevant		
Flash point:	< 0 ° C		
Evaporation rate:	Not Relevant		
Solid/gas flammability:	Not Relevant		
Upper/lower flammability or explosive limits:	Not Relevant		
Vapour pressure:	5 BAR +/- 1 15°C		
Vapour density:	>2		
Relative density:	0.800 kg/l +/- 0.05		
Solubility in water:	Not Relevant		
Solubility in oil:	Not Relevant		
Partition coefficient (n- octanol/water):	Not Relevant		
Auto-ignition temperature:	>175°C		
Decomposition temperature:	Not Relevant		
Viscosity:	Not Relevant		
Explosive properties:	section 10.3		

Oxidizing properties:	Not Relevant	

9.2. Other information

Properties	Value	Method:	Notes:
kinematic viscosity:	Not Relevant		
Miscibility:	Not Relevant		
Fat Solubility:	Not Relevant		
Conductivity:	Not Relevant		
Substance Groups relevant properties	Not Relevant		

SECTION 10: Stability and reactivity

10.1. Reactivity

avoid contact with strong acids and bases and oxidizing agents.

- 10.2. Chemical stability Stable under normal conditions
- 10.3. Possibility of hazardous reactions avoid mixing the product with strong oxidizers and strong acids may form explosive vapor / air mixtures in places not well ventilated
- 10.4. Conditions to avoid avoid the accumulation of electrostatic charges. keep away from heat, sources of ignition
- 10.5. Incompatible materials oxidizing agents acids, alkalis and alkaline metals
- 10.6. Hazardous decomposition products the product is flammable, following combustion can lead to the formation of dangerous decomposition products by thermal decomposition can rid COx during combustion it produces irritating gases

SECTION 11: Toxicological information

11.1. Information on toxicological effects Toxicological information of the product: DETERGENTE IGIENIZZANTE TESSUTI E SUPERFICI DURE a) acute toxicity Not classified Based on available data, the classification criteria are not met b) skin corrosion/irritation Not classified Based on available data, the classification criteria are not met c) serious eye damage/irritation The product is classified: Eye Irrit. 2 H319 d) respiratory or skin sensitisation The product is classified: Skin Sens. 1 H317 e) germ cell mutagenicity Not classified Based on available data, the classification criteria are not met f) carcinogenicity Not classified Based on available data, the classification criteria are not met g) reproductive toxicity

MIXIPAIGIEN/3 Page n. 8 of 13

Not classified
Based on available data, the classification criteria are not met
h) STOT-single exposure
The product is classified: STOT SE 3 H336
i) STOT-repeated exposure
Not classified
Based on available data, the classification criteria are not met
j) aspiration hazard
Not classified
Based on available data, the classification criteria are not met
Toxicological information of the main substances found in the product:
propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat > 5840 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg
butanone; ethyl methyl ketone - CAS: 78-93-3
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat > 2000 mg/kg
Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg
DETERGENTE IGIENIZZANTE TESSUTI E SUPERFICI DURE -
Irritabilità primaria
Il contatto ripetuto o prolungato con la pelle può provocare dermatosi o disseccamenti
Occhi: opacità corneale (2 animali > 1) e arrossamento congiuntivale (2 animali > 2).
Test su coniglio (OECD 405). Provoca grave irritazione oculare.
ethanol; ethyl alcohol - CAS: 64-17-5
LD50 (RABBIT) ORAL: 6300 MG/KG
LD50 (RAT) ORAL SINGLE DOSE: 7060 MG/KG

SECTION 12: Ecological information

12.1. Loxicity
Adopt good working practices, so that the product is not released into the environment. VOC: Sì
DETERGENTE IGIENIZZANTE TESSUTI E SUPERFICI DURE
Not classified for environmental hazards
Based on available data, the classification criteria are not met
propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
a) Aquatic acute toxicity:
Endpoint: EL50 - Species: Daphnia > 100 mg/l - Duration h: 48
Endpoint: EL50 - Species: Algae > 100 mg/l - Duration h: 72
Endpoint: EL50 - Species: Fish > 100 mg/l - Duration h: 48
butanone; ethyl methyl ketone - CAS: 78-93-3
a) Aquatic acute toxicity:
Endpoint: EL50 - Species: Daphnia = 308 mg/l - Duration h: 48
Endpoint: EL50 - Species: Algae = 2029 mg/l - Duration h: 96
Endpoint: LC50 - Species: Fish = 2993 mg/l - Duration h: 96
12.2. Persistence and degradability
None
butanone; ethyl methyl ketone - CAS: 78-93-3
Biodegradability: Not persistent and Biodegradable
12.3. Bioaccumulative potential
butanone; ethyl methyl ketone - CAS: 78-93-3

MIXIPAIGIEN/3 Page n. 9 of 13

Bioaccumulation: Not bioaccumulative

- 12.4. Mobility in soil
 - butanone; ethyl methyl ketone CAS: 78-93-3 Mobility in soil: Mobile
- 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Additional disposal information:

contaminated packaging should be sent for recovery or disposal in compliance with national regulations on waste management

reuse if possible. Product residues are to be considered hazardous waste. disposal must be entrusted to authorised waste management, in compliance with national and, where appropriate, local. CER 160504

SECTION 14: Transport information

14.1. UN number	
ADR-UN number:	1950
IATA-Un number:	1950
IMDG-Un number:	1950
14.2. UN proper shipping name	
14.3. Transport hazard class(es)	
ADR-Class:	2.5°F CAP. 2.2.2.1.6 UN1950
IATA-Class:	2.1
IMDG-Class:	2 Aerosols UN 1950
14.4. Packing group	
ADR-Packing Group:	N.A.
IATA-Packing group:	N.A.
IMDG-Packing group:	N.A.
14.5. Environmental hazards	
Marine pollutant:	No
14.6. Special precautions for user	
IMDG-Page:	2102
14.7. Transport in bulk according to A	Annex II of Marpol and the IBC Code

SECTION 15: Regulatory information

No

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 944/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)

MIXIPAIGIEN/3 Page n. 10 of 13

Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Regulation (EU) n. 2016/918 (ATP 8 CLP) Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: None Where applicable, refer to the following regulatory provisions : Directive 2012/18/EU (Seveso III) Regulation (EC) nr 648/2004 (detergents). Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 Product belongs to category: P3a

15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Text of phrases referred to under heading 3:

H220 Extremely flammable gas.

- H280 Contains gas under pressure; may explode if heated.
- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H226 Flammable liquid and vapour.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.
- H314 Causes severe skin burns and eye damage.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H331 Toxic if inhaled.

Hazard class and hazard category	Code	Description
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Press. Gas	2.5	Gases under pressure
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 3	3.1/3/Dermal	Acute toxicity (dermal), Category 3
Acute Tox. 3	3.1/3/Inhal	Acute toxicity (inhalation), Category 3
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1
Skin Sens. 1,1A,1B	3.4.2/1-1A-1B	Skin Sensitisation, Category 1,1A,1B
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure,

		Category 3
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 2	4.1/C2	Chronic (long term) aquatic hazard, category 2

Paragraphs modified from the previous revision:

SECTION 3: Composition/information on ingredients SECTION 8: Exposure controls/personal protection SECTION 11: Toxicological information SECTION 12: Ecological information SECTION 16: Other information

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222+H229	On basis of test data
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
STOT SE 3, H336	Calculation method

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of
	Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.

MIXIPAIGIEN/3 Page n. 12 of 13

INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods
	by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.